



HEAVY DUTY OPEN TOP ROLL-OFF CONTAINER

SPECIFICATIONS

SIDES.....	3/16"
FLOOR.....	1/4"
UNDERSTRUCTURE.....	3" STRUCTURAL CHANNEL
SPACING.....	12" ON CENTER, GUSSETED 24" ON CTR
LONG SILLS	6" X 2" X 1/4" TUBE
TOP RAIL.....	4" X 3" X 3/16" TUBE
UPRIGHTS.....	3" X 5" X 3" / 24" ON CENTER
HOOK PLATE.....	3/4" HOOK PLATE W/ 1/4" GRAB HOOK
FRONT CORNER POST..	3' X 5"
WHEELS.....	8" X 10" STEEL WHEELS
WHEEL AXLES.....	1 3/8" STANDARD W/ GREASE FITTINGS
PAINT.....	PPG ALKYD ENAMEL PRIMER & PAINT
LATCH SYSTEM	RATCHET

OPTIONS

- INVERTED ANGLE
- PUSH PLATE
- INTERIOR CLEANOUTS
- SIDE STIFFNERS
- SEALED GATE
- SUMP
- HARDOX FLOOR & SIDES

DURABLE. DEPENDABLE. DESIGNED FOR YOU.