



DOUBLE LID SLUDGE CONTAINER



SPECIFICATIONS

SIDES ...	3/16"
FLOOR ...	1/4"
UNDERSTRUCTURE ...	3" STRUCTURAL CHANNEL
SPACING ...	15" ON CENTER
LONG SILLS ...	6" X 2" X 1/4" TUBE
TOP RAIL ...	4" X 3" X 3/16" TUBE
GATE ...	SEALED W/ DOUBLE RATCHET
HOOK PLATE ...	3/4" HOOK PLATE W/ 1 1/4" GRAB HOOK
HINGE SYSTEM	FLOATING
WHEELS ...	8" X 9" STEEL WHEELS
WHEEL AXLES ...	1 1/2" STANDARD W/ GREASE FITTINGS
PAINT ...	PPG ALKYD ENAMEL PRIMER & PAINT
LATCH SYSTEM ...	HANDLE & GRADE 80 V-CHAIN W/ PIN & CLEVIS

OPTIONS

- DRAINS
- DEWATERING CAGE

PLEASE ASK YOUR SALES REP
FOR ALL AVAILABLE OPTIONS

STANDARDS LISTED APPLY TO 20, 30, 40 YARD CONTAINERS

DURABLE. DEPENDABLE. DESIGNED FOR YOU.