



HEAVY DUTY OPEN TOP ROLL-OFF CONTAINER



SPECIFICATIONS

SIDES ...	3/16"
FLOOR ...	1/4"
UNDERSTRUCTURE ...	3" STRUCTURAL CHANNEL
SPACING ...	12" ON CENTER
LONG SILLS ...	6" X 2" X 1/4" TUBE
TOP RAIL ...	4" X 3" X 3/16" TUBE (BULKHEAD 1/8")
UPRIGHTS ...	3" X 5" W/ 24" ON CENTER
HOOK PLATE ...	3/4" HOOK PLATE W/ 1 1/4" GRAB HOOK
FRONT CORNER POST ...	3" X 5" X 10GA
WHEELS ...	8" X 9" STEEL WHEELS
WHEEL AXLES ...	1 1/2" STANDARD W/ GREASE FITTINGS
PAINT ...	PPG ALKYD ENAMEL PRIMER & PAINT
LATCH SYSTEM ...	HANDLE
PUSH PLATE ...	1/4" STANDARD

OPTIONS

- INVERTED ANGLE
- SIGN PLATE
- DIRT SHEDDERS
- CLEANOUTS
- V-CHAIN
- RATCHET LATCH

PLEASE ASK YOUR SALES REP
FOR ALL AVAILABLE OPTIONS

STANDARDS LISTED APPLY TO 20, 30, 40 YARD CONTAINERS

DURABLE. DEPENDABLE. DESIGNED FOR YOU.