

VAC TANK



SPECIFICATIONS

SIDES ... 1/4" FLOOR ... 1/4"

UNDERSTRUCTURE ... 4" X 3" X 3/16" TUBE LONG SILLS ... 6" X 2" X 1/4" TUBE BOLSTERS ... 4" X 3" X 3/16"

GATE ... SEALED WITH DOUBLE RATCHET

HOOK PLATE ... 3/4" HOOK PLATE W/ 11/4" GRAB HOOK

HINGE ... FLOATING HINGE W/ V-CHAIN

WHEELS ... 8" X 9" STEEL WHEELS

WHEEL AXLES ... 11/2" STANDARD W/ GREASE FITTINGS PAINT ... PPG ALKYD ENAMEL PRIMER & PAINT

LATCH SYSTEM ... HANDLE & GRADE 70 V-CHAIN

W/ PIN & CLEVIS

OPTIONS

- BULKHEAD PROTECTION WITH HD FRONT PUSH PLATE
- 21" MAN-WAY INSPECTION
- EXPANDED METAL PLATFORM W/ SAFETY HANDLES
- 24" INSPECTION LADDER
- 8" OUTLETS ON BULKHEAD AND TAILGATE

PLEASE ASK YOUR SALES REP FOR ALL AVAILABLE OPTIONS

STANDARDS LISTED APPLY TO 20, 30, 40 YARD CONTAINERS

DURABLE. DEPENDABLE. DESIGNED FOR YOU.