



WASTE OPEN TOP ROLL-OFF CONTAINER



SPECIFICATIONS

SIDES ...	12 GAUGE
FLOOR ...	3/16"
UNDERSTRUCTURE ...	3" STRUCTURAL CHANNEL
SPACING ...	20" ON CENTER, 40" CTR
LONG SILLS ...	6" X 2" X 3/16" TUBE
TOP RAIL ...	4" X 3" X 1/8" TUBE
UPRIGHT ...	3" X 5" W/ 30" ON CENTER
HOOK PLATE ...	3/4" HOOK PLATE W/ 1 1/4" GRAB HOOK
FRONT CORNER POST ...	6" X 6" x 10GA
WHEELS ...	8" X 9" STEEL WHEELS
WHEEL AXLES ...	1 1/2" STANDARD W/ GREASE FITTINGS
PAINT ...	PPG ALKYD ENAMEL PRIMER & PAINT
LATCH SYSTEM ...	HANDLE TYPE

OPTIONS

- INVERTED ANGLE
- SIGN PLATE
- DIRT SHEDDERS
- CLEANOUTS
- V-CHAIN
- RATCHET LATCH

PLEASE ASK YOUR SALES REP
FOR ALL AVAILABLE OPTIONS

STANDARDS LISTED APPLY TO 20, 30, 40 YARD CONTAINERS

DURABLE. DEPENDABLE. DESIGNED FOR YOU.